

The **Cool-Lam® 640C** laminator is a perfect match for your wide format finishing needs when high quality professional graphics are required. Ideal for mounting and laminating pressure-sensitive solutions up to 63", this machine represents a new level for price performance at an affordable price!

The **Cool-Lam® 640C** is a pressure sensitive, cold laminator ideal for materials that are sensitive to heat. Designed to protect a broad variety of inkjet output, the **Cool-Lam® 640C** can laminate and mount prints up to 63" wide using pressure-sensitive films and mounting adhesives. Designed to be easy to use, the **Cool-Lam® 640C** provides all the features needed for the most experienced operators.

The Cool-Lam® Series focus on simplicity and affordability are great for businesses wishing to introduce application solutions to their customers or wishing to complement existing laminating facilities. With its elegant design, a Cool-Lam® rolls anywhere it is needed, or stores neatly out of the way.

Features

- Simple 3-button operation
- Single set main rollers
- Powered take-up shafts
- Foot pedal operation
- Rewind for release liner
- Hex steel supply shaft
- Easy-to-clean silicone rollers
- Motor-reverse function
- Photo beam safety system
- Removable feed tray
- Includes floor stand



Powered liner take-up assist in media handling.



Easy to use front panel and simple nip adjust level.

The Cool-Lam 640C can apply a range of pressure - sensitive laminates for a variety of applications including vehicle graphics, architectural signage, POP and trade show displays and photographic output. It handles flexible as well as rigid substrates up to a 1/2" thick.



Specifications

Maximum Film Width	62"
Maximum Material Thickness	1/2"
Speed	0 - 10' / Minute
Maximum Film Roll Diameter	6"
Core Size	3"
Usable Films	PSA Films and Adhesives
Unwind / Rewind Shafts	2 Unwinds / 1 Top Rewind
Model Dimensions	72.25" W x 48" H x 26.5" D
Machine Weight	385 lbs.
Crated Dimensions	W 80" x H 55" x D 32"
Crated Weight	460 lbs.
Electrical Requirements	120 VAC, 1.7 Amps, 200 W
Safety	UL / CSA
Plug Configuration	NEMA 5-15R
Warranty	1 Year Parts / 90 Days Labor