



GMI SPM400FW/P
Matte White Calendered Vinyl
4.3 – 4.5 MILS. WITH ADHESIVE
With a Clear Permanent Acrylic Adhesive
For Eco-Solvent, Solvent and UV-Solvent Based Inkjet Printers.

GMI's premium vinyl is ideal for indoor and outdoor applications. For outdoor use it is recommended that an overlamine be used to protect printed image.

CONSTRUCTION

Applications	This product is intended for use in high quality interior/exterior marking or decal applications requiring block out or opacity such as bumper stickers, point of purchase decals, fleet markings and decals.
Face Film	4.0 Mil
Adhesive Release	50 oz/in.
Liner	90#

PHYSICAL PROPERTIES

Outdoor Durability	Up to 5 years mid-continental U.S. vertical.																
Print Methods	Digital inkjet and screen printing process.																
Minimum Surface/Ambient Air Application Temperature	+ 50° F																
Service Temperature Range	+ 50° F to 140° F																
Opacity	Good.																
Typical Film Caliper (w/Adhesive)	4.3 Mil to 4.5 Mil																
Product Thickness	4.0 Mil face film																
Chemical Resistance	Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended																
Water Resistance	Excellent: test piece aged 24 hours after application to stainless steel panel before testing. Not affected when immersed in 70 F water for seven days.																
Finish	Matte.																
Shelf Life	1 year when stored under conditions of 70° F and 50% relative humidity.																
Sizes	<table border="1"> <tr><td>SPM400FW/P3025</td><td>30" X 25 YDS</td></tr> <tr><td>SPM400FW/P3050</td><td>30" X 50 YDS</td></tr> <tr><td>SPM400FW/P3625</td><td>36" x 25 YDS</td></tr> <tr><td>SPM400FW/P3650</td><td>36" x 50 YDS</td></tr> <tr><td>SPM400FW/P5425</td><td>54" x 25 YDS</td></tr> <tr><td>SPM400FW/P5450</td><td>54" x 50 YDS</td></tr> <tr><td>SPM400FW/P6025</td><td>60" x 25 YDS</td></tr> <tr><td>SPM400FW/P6050</td><td>60" x 50 YDS</td></tr> </table>	SPM400FW/P3025	30" X 25 YDS	SPM400FW/P3050	30" X 50 YDS	SPM400FW/P3625	36" x 25 YDS	SPM400FW/P3650	36" x 50 YDS	SPM400FW/P5425	54" x 25 YDS	SPM400FW/P5450	54" x 50 YDS	SPM400FW/P6025	60" x 25 YDS	SPM400FW/P6050	60" x 50 YDS
SPM400FW/P3025	30" X 25 YDS																
SPM400FW/P3050	30" X 50 YDS																
SPM400FW/P3625	36" x 25 YDS																
SPM400FW/P3650	36" x 50 YDS																
SPM400FW/P5425	54" x 25 YDS																
SPM400FW/P5450	54" x 50 YDS																
SPM400FW/P6025	60" x 25 YDS																
SPM400FW/P6050	60" x 50 YDS																

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2006 Graphic Materials International. All rights reserved. SPM400FW/P 063006