

GMI SPMRF Reflective Vinyl 7.0 Mil White Reflective Vinyl



SPMRF is a flexible, enclosed lens glass-bead retroreflective sheeting with removable adhesive.

CONSTRUCTION

Applications	Typical applications for this material are vehicle markings where application to riveted and corrugated surfaces may be required. It can also be used on commercial signs and various labels and is highly resistant against to extremes of hot, cold, dry and humid weathering conditions. This type of sheeting conforms to ASTM D4956 TYPE I Specifications.
Adhesive Release	Removal performance is up to 3 years.
Liner	78 # Kraft Liner

PHYSICAL PROPERTIES

Outdoor Durability	Film up to 5 years.																								
Minimum Surface/Ambient Air Application Temperature	Minimum 20° C.																								
Printing Methods	Digital printing with use of Eco-solvent and solvent inks and most screen printing inks.																								
Application Surface	Minimum application temperature for flat surfaces 15°C, for corrugated and riveted surfaces 25°C.																								
Opacity	Excellent.																								
Typical Film Caliper (w/Adhesive)	.13mm																								
Elongation	> 120%																								
Chemical Resistance	Excellent.																								
Water Resistance	Excellent.																								
Adhesion	Permanent bonding will take place approximately 48 hours after application.																								
Finish	Gloss meter >85 @ 60 degrees																								
Shelf Life	12 months when properly stored under conditions of 70°F and 50% humidity.																								
Sizes	<table><tr><td>SPMRF2410</td><td>24" X 10 YDS</td><td>SPMRF3610</td><td>36" X 10 YDS</td></tr><tr><td>SPMRF2425</td><td>24" X 25 YDS</td><td>SPMRF3625</td><td>36" X 25 YDS</td></tr><tr><td>SPMRF2450</td><td>24" X 50 YDS</td><td>SPMRF3650</td><td>36" X 50 YDS</td></tr><tr><td>SPMRF3010</td><td>30" X 10 YDS</td><td>SPMRF4810</td><td>48" X 10 YDS</td></tr><tr><td>SPMRF3025</td><td>30" X 25 YDS</td><td>SPMRF4825</td><td>48" X 25 YDS</td></tr><tr><td>SPMRF3050</td><td>30" X 50 YDS</td><td>SPMRF4850</td><td>48" X 50 YDS</td></tr></table>	SPMRF2410	24" X 10 YDS	SPMRF3610	36" X 10 YDS	SPMRF2425	24" X 25 YDS	SPMRF3625	36" X 25 YDS	SPMRF2450	24" X 50 YDS	SPMRF3650	36" X 50 YDS	SPMRF3010	30" X 10 YDS	SPMRF4810	48" X 10 YDS	SPMRF3025	30" X 25 YDS	SPMRF4825	48" X 25 YDS	SPMRF3050	30" X 50 YDS	SPMRF4850	48" X 50 YDS
SPMRF2410	24" X 10 YDS	SPMRF3610	36" X 10 YDS																						
SPMRF2425	24" X 25 YDS	SPMRF3625	36" X 25 YDS																						
SPMRF2450	24" X 50 YDS	SPMRF3650	36" X 50 YDS																						
SPMRF3010	30" X 10 YDS	SPMRF4810	48" X 10 YDS																						
SPMRF3025	30" X 25 YDS	SPMRF4825	48" X 25 YDS																						
SPMRF3050	30" X 50 YDS	SPMRF4850	48" X 50 YDS																						

*100 & 200 YD rolls available upon request.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2008 Graphic Materials International.
All rights reserved. SPMRF 050408.