



**GMI SPMWOG
Walk-On Graphics®**

**4.0 Mil White or Clear Flexible Vinyl Base Film and
6.5 Mil Clear Embossed Rigid Vinyl Overlaminates
with Permanent Adhesive on a Clear Film Release Liner
For Eco-Solvent, Solvent and UV-Solvent Based Inkjet Printers.**

The WALK-ON GRAPHICS KIT is composed of one roll overlamination film, which is slip resistant film used for protection of the graphics, and a vinyl base film used for printing. Both of these films are coated with a pressure sensitive adhesive for use in cold laminating applications.

CONSTRUCTION

Applications	Walk-On Graphics was developed for floor application in advertising, graphics and messages and can be temporarily used for up to 6 months under normal wear and tear.
Base Film	Walk-On Graphics uses a white or clear flexible vinyl with a high performance removable acrylic adhesive. This film is available non-top coated for screen and digital printing using solvent and eco-solvent inks.
Overlaminates	The overlaminates are an embossed vinyl or polypropylene, or a clear high polished vinyl with a permanent adhesive that is applied to the printed decal with a cold laminating process. The overlaminates are UL approved for slip resistance.
Adhesive Release	Removeable
Liner	90# Stayflat

PHYSICAL PROPERTIES

Outdoor Durability	Interior use only										
Print Methods	Screen or digital printing processes using eco-solvent or solvent inks.										
Application Procedure	Remove the release film liner from the back of the graphic and position it on the desired location of the floor. Lift one edge of the decal. Using a squeegee with overlapping strokes, apply pressure from the middle toward the edge of the decal. If the decal is large, it is recommended to spray the floor with water mixed with a few drops of liquid soap and follow the above procedure. It is important that all edges and corners are applied with firm pressure. When more than one panel is used, butt the edges together. Never overlap the decal (s). After application is completed, do not polish decals or surrounding floor for 24 hours. If the edges lift at all from the floor, the decal must be removed immediately and replaced. This is to prevent any accident or tripping.										
Maintenance	Maintain using normal floor maintenance procedures.										
Removal	Remove by lifting one edge and pulling at a sharp angle using short sharp strokes until the decal is up. If the decal is applied to a waxed floor, it is recommended that the floor be rewaxed										
Recommended Floor Surfaces for Application	Tile Floors, Ceramic Tile, Sealed Concrete, Sealed Wood, Waxed Vinyl										
Sizes	<table border="1"> <tr><td>SPMWOG2725</td><td>27" X 25 YDS</td></tr> <tr><td>SPMWOG2750</td><td>27" X 50 YDS</td></tr> <tr><td>SPMWOG5425</td><td>54" X 25 YDS</td></tr> <tr><td>SPMWOG5450</td><td>54" X 50 YDS</td></tr> <tr><td>SPMWOG54100</td><td>54" X 100 YDS</td></tr> </table>	SPMWOG2725	27" X 25 YDS	SPMWOG2750	27" X 50 YDS	SPMWOG5425	54" X 25 YDS	SPMWOG5450	54" X 50 YDS	SPMWOG54100	54" X 100 YDS
SPMWOG2725	27" X 25 YDS										
SPMWOG2750	27" X 50 YDS										
SPMWOG5425	54" X 25 YDS										
SPMWOG5450	54" X 50 YDS										
SPMWOG54100	54" X 100 YDS										

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

☎ If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.
🌐 Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2006 Graphic Materials International.
All rights reserved. SPMWOG 071206